

Clean Set of Amended Claims

- Sub E17  
B1
1. (Amended) A cochlear implant system, comprising:  
a signal generator that generates a second signal capable of causing pseudospontaneous activity in an auditory nerve;  
a signal processor that combines a first signal that represents sound and the second signal to output a combined signal; and  
a stimulation unit coupled to the signal processor that receives the combined signal from the signal processor.
  2. (Amended) The system according to claim 1, wherein the stimulation unit is an electrode array unit that is coupled to the auditory nerve.

- Sub E17  
B2
4. (Amended) The system according to claim 1, wherein the second signal includes one of (i) a pulse train generating substantially continuous pseudospontaneous activity, (ii) a broad band noise, and (iii) at least fluctuations in amplitude greater than prescribed amount at a frequency above approximately 2k Hz that causes statistically independent activity in a plurality of nerve fibers of the nerve.

~~Sub E17~~  
~~B2~~ 5. (Amended) The system according to claim 1, wherein the pseudospontaneous activity is demonstrated by statistically independent activity in a plurality of nerve fibers in the auditory nerve.

---

~~Sub E17~~  
~~B3~~ 10. (Amended) The system according to claim 1, wherein a microphone, the signal processor and the signal generator are positioned external to an ear, wherein the stimulation unit is coupled by a wire to the signal processor, and wherein the stimulation unit is coupled to the auditory nerve via a cochlea.

---

~~Sub E17~~  
~~B4~~ 13. (Amended) The method according to claim 11, wherein the first signal represents at least one of speech, emergency signals and control information.

---

~~Sub E17~~  
~~B5~~ 14. (Amended) The method according to claim 12, wherein an inner ear implant is capable of performing the steps of receiving through applying.

---

~~Sub E17~~  
~~B5~~ 16. (Amended) An auditory prosthesis for receiving an auditory signal representing sound and supplying an electrical signal which is adapted to stimulate the auditory nerve of a person, comprising:

pseudospontaneous generation means for generating a pseudospontaneous driving

5 signal;

E1  
BS  
transducer means adapted to receive the auditory signal and the  
pseudospontaneous driving signal for transforming the auditory signal and the  
pseudospontaneous driving signal to an electrical input signals; and

10 stimulation means, operatively coupled to the electrical input signals generated by  
the transducer means, for stimulating the auditory nerve at defined locations within the cochlea,  
wherein at least one of the plurality of electrical signals is capable of causing statistically  
independent activity in a plurality of nerve fibers of an auditory nerve.

SUB  
D1  
BC  
18. (Amended) The auditory prosthesis of claim 16, wherein the pseudospontaneous  
driving signal includes one of (i) a pulse train generating substantially continuous activation, (ii)  
a broad band noise, or (iii) at least fluctuations in amplitude greater than prescribed amount at  
a frequency above approximately 2k Hz.

**B. Please add new claims 19-31 as follows:**

Sub E1 19. (New) The method of claim 14, wherein the applying the combined signal generates substantially continuous pseudospontaneous activity.

20. (New) The method of claim 11, wherein the second signal is not continuously applied.

37  
Sub D2 21. (New) The method of claim 11, wherein the second signal includes one of (i) a pulse train generating substantially continuous pseudospontaneous activity, (ii) a broad band noise, and (iii) at least fluctuations in amplitude greater than prescribed amount at a frequency above approximately 2k Hz that causes statistically independent activity in a plurality of nerve fibers of the nerve.

Sub C1 22. (New) A neural prosthetic apparatus, comprising:  
a signal generator that generates a second signal capable of inducing a random pattern of activation in an auditory nerve;  
a signal processor that combines a first signal that represents sound and the second signal to output a combined signal; and  
stimulation unit coupled to the signal processor that receives the combined signal from the signal processor for application to the auditory nerve.

Sub E17 23. (New) The apparatus according to claim 22, wherein the stimulation unit is an electrode array unit that is coupled to the auditory nerve, and wherein the first signal is applied to a first subset of electrodes in the electrode array and the second signal is applied to a second subset of electrodes in the electrode array.

B7  
SUB  
C2 24. (New) The apparatus according to claim 22, wherein the random pattern of activation is demonstrated by statistically independent activity in a plurality of nerve fibers in the auditory nerve.

Sub E17 25. (New) The apparatus according to claim 22, wherein the auditory nerve comprises a plurality of nerve fibers, and wherein the second signal comprises one or more signals that generate a substantially maximum firing rate of the plurality of nerve fibers.

54B  
e3 26. (New) The apparatus according to claim 22, wherein the second signal includes one of (i) a pulse train generating substantially continuous pseudospontaneous activity, (ii) a broad band noise, and (iii) at least fluctuations in amplitude greater than prescribed amount at a frequency above approximately 2k Hz that causes statistically independent activity in a plurality of nerve fibers of the nerve.

543  
D3  
27. (New) The apparatus according to claim 22, wherein the prosthesis is a cochlear implant applying current to the auditory nerve.

Sub E17  
28. (New) The apparatus according to claim 22, wherein the pseudospontaneous activity continues after the second signal is stopped.

B7  
29. (New) A method of modifying a neural prosthetic apparatus that receives an information signal and supplies a corresponding electrical signal to stimulate an auditory nerve, comprising:

providing a pseudospontaneous signal generator that generates a second signal;

5 and

providing an electrical coupling means for supporting an electrical connection from the pseudospontaneous signal generator to at least one electrical contact, and wherein the second signal is capable of inducing a random pattern of activation in the auditory nerve mimicking the spontaneous neural activity of the auditory nerve.

Taught by Loeb  
30. (New) The method of claim 29, wherein the information signal represents at least one of speech, emergency signals and control information, and wherein the second signal includes one of (i) a pulse train generating substantially continuous pseudospontaneous activity, (ii) a broad band noise, (iii) at least fluctuations in amplitude greater than prescribed amount at

81  
87 a frequency above approximately 2k Hz, and (iv) at least fluctuations in amplitude greater than prescribed amount at a frequency that causes statistically independent activity in a plurality of nerve fibers of the auditory nerve.

543  
D4 31. (New) The method of claim 29, wherein the neural prosthetic apparatus is a cochlear implant.